1

INTEGRATED ENGINE/COMPRESSOR CONTROL
FOR GAS TRANSMISSION COMPRESSORS

TECHNICAL FIELD OF THE INVENTION

This invention relates to large compressor/engine units for transporting natural gas, and more particularly for the control systems for this type of compressor unit.

5

BACKGROUND OF THE INVENTION

Most natural gas consumed in the United States is not produced in the areas where it is most needed. To get gas from increasingly remote production sites to consumers, pipeline companies operate and maintain hundreds of thousands of miles of main transmission lines. This gas is then sold to local distribution companies, who deliver gas to consumers using a network of more than a million miles of local distribution lines. This vast underground transmission and distribution system is capable of moving many billions of cubic feet of gas each day. To provide force to move the gas, and to improve the economics of gas transportation, operators install large compressors at transport stations along each pipeline.

These compressors can be driven by various engines and motors. Compressors driven by natural gas engines have proved to reduce power demand and energy consumption costs, as compared to compressors driven by other means. An advantage of these engines is that they are driven by the same natural gas as is being transported by the compressor.

Conventionally, the control systems for the engine and compressor are isolated from each other. That is, the engine control system does not receive data about what the compressor control system is doing, and vice versa.

SUMMARY OF THE INVENTION

One aspect of the invention is a method of controlling an internal combustion engine that drives a reciprocating gas compressor. It is assumed that the compressor's output is controlled by specifying "load steps" for its cylinders. A "integrated" engine/compressor controller receives various compressor operating values, which include at least the compressor load step for each cylinder, the compressor suction pressure, and the compressor discharge pressure. Optionally, the controller may also receive various engine operating values.

Based on these operating values, the controller calculates engine and/or compressor control parameters. Many different control parameters are possible as outputs from the controller, but typically the controller will control at least the air flow to the engine. Other likely control parameters include spark timing for engine ignition, and various engine fuel parameters.

The controller can be programmed to provide these parameters on the basis of any desired engine optimization. For example, the engine control parameters can be calculated so as to maximize engine efficiency and/or minimize emissions.

BRIEF DESCRIPTION OF THE DRAWINGS

A more complete understanding of the present embodiments and advantages thereof may be acquired by referring to the following description taken in conjunction with the accompanying drawings, in which like reference numbers indicate like features, and wherein:

FIGURE 1 illustrates an engine-driven compressor system having a integrated engine/compressor controller in accordance with the invention.

FIGURE 2 illustrates a compressor system in which the engine and compressor are separable, but with which the controller of FIGURE 1 may also be used.

FIGURE 3 illustrates one of the compressor cylinders of FIGURE 1, with load pockets and load valves used for load step control.

FIGURE 4 illustrates how compressor load steps affect the engine in terms of its NOx emissions and thermal efficiency.

DETAILED DESCRIPTION OF THE INVENTION

FIGURE 1 illustrates an engine-driven compressor system 100, having an integrated engine/compressor controller 17 in accordance with the invention.

5   Compressor system 100 is an "integrated engine-compressor system" in the sense that its engine 11 and compressor 12 share the same crankshaft 13.

The engine 11 is represented by three engine cylinders 11a - 11c. The compressor 12 is represented by

10   four compressor cylinders 12a - 12d. In practice, engine 11 and compressor 12 may each have many more cylinders.

FIGURE 2 illustrates a compressor system 200 in which the engine 21 and compressor 22 are separate units. This engine/compressor configuration is referred to

15   herein as a "separable engine-compressor system". The respective crankshafts 23 of engine 21 and compressor 22 are mechanically joined at a gearbox 24, which permits the engine to drive the compressor.

As indicated in the Background, a typical

20   application of gas compressor systems 100 and 200 is in the gas transmission industry. Both systems 100 and 200 are characterized by having a reciprocating compressor 13 or 23, whose output is controlled by specifying "load steps' for its compressor cylinders. For purposes of

25   this description, the engine cylinders are referred to as the "power cylinders" of system 100 or system 200.

The following description is written in terms of the integrated system 100 and its components. The same concepts are applicable to system 200; as indicated in

30   FIGUREs 1 and 2, the same controller 17 may be used with either type of system.

Controller 17 is equipped with processing and memory devices, appropriate input and output devices, and an appropriate user interface. It is programmed to perform the various control tasks described herein, and deliver

5   control parameters to the engine 11 and compressor 12.

Controller 17 receives output specifications that specify operating parameters, such as a desired discharge pressure for compressor 100. It also receives operating data from engine 11 and compressor 12. This input data

10   may be measured data from various sensors (not shown) or data from other control devices associated with engine 11 or compressor 12.

As explained below, controller 17 adjusts various engine control parameters that are affected by compressor

15   load step variations and the resulting variations in the load induced on the engine crankshaft by the compressor. These engine parameters may be adjusted to maximize engine operation in terms of combustion and emissions. Given the input data, output specifications, and control

20   objectives described herein, algorithms for programming controller 11 may be developed and executed.

In the examples of FIGUREs 1 and 2, controller 17 controls engine 11 and compressor 12 directly. In other embodiments, controller 17 could be remote from the

25   engine/compressor equipment, and control parameters could be delivered over a data communications link, such as a network. A networked link of this type would permit the networking of a controller 17 with a remote station control system.

30   As indicated in the Background, internal combustion engine 11 is used as the compressor driver. That is, the

engine's horsepower is unloaded through the compressor. In the example of this description, engine 11 is a natural gas engine, but the same concepts could apply to engines using other fuels.

5   Compressor 12 operates between two gas transmission lines. A first line, at a first pressure, is referred to as the suction line. A second line, at a second pressure, is referred to as the discharge line. Typically, the suction pressure and discharge pressure

10   are measured in psi (pounds per square inch). In practical application, gas flow is determined by specifying a desired flow in terms of psi on the discharge line.

       The power requirement of the gas compressor 100 is

15   adjusted in terms of "load steps". Load steps are achieved by using discrete unloaders, such as the "load pockets" described below, or by using infinitely variable (stepless) unloaders. The term "load step" as used herein encompasses the parameter for specifying power

20   requirements of any of these types of compressor unloaders.

       FIGURE 3 illustrates one of the compressor cylinders 12a - 12d of FIGURE 1, with load pockets and load valves used for load step control. Each end (head and crank) of

25   cylinder 12a has two load pockets 31. A valve 32 is used to either open or close the opening between the pocket 31 and the cylinder. In this example, each of four load pockets 31 has a capacity of one-quarter of the gas compressed by cylinder 31 in one stroke. The pockets

30   change the compression ratio of the compressor 12, and

thus the power required by the engine 11 to drive the
compressor cylinders.

   As engine 11 operates, the load on engine 11 induced
by compressor 12 continually varies over the engine
5   cycle. Factors that contribute to the instantaneous load
on the engine crankshaft 13 include the phasing between
the power cylinders and the compressor cylinders, the
number of compressor cylinders, the compressor type
(i.e., whether single acting, double acting, etc.), the
10   unit loading scheme, and the number of discrete load
steps.

   Some power cylinders carry larger loads than others
based on a particular load step. An engine crankshaft
load that is poorly distributed among the power cylinders
15   11a - 11c can lead to poor engine performance and to
crankshaft failure.

   For automotive engines, studies have shown that the
instantaneous crank angle velocity (ICAV) decreases for a
brief period of time as the power cylinder piston
20   approaches top-dead-center (TDC) during its compression
stroke. The piston is then accelerated during the power
stroke following combustion. Likewise, for gas
compressor engines such as engine 11, studies have shown
that ICAV decreases as the power cylinders approach TDC.
25   This effect is exacerbated with the addition of the
compressor-induced load, a load that varies throughout
the engine cycle.

   The number and geometric arrangement of the
compressor cylinders 12a - 12d relative to the power
30   cylinders 11a - 11c directly influences the acceleration
and deceleration of some power cylinders relative to

others. For example, if all compressor cylinders are
loaded equally, and if the geometrical arrangement is
such that a compressor cylinder is nearing TDC at or near
the same time as an power cylinder, that power cylinder
5 will experience more deceleration.

FIGURE 4 illustrates how compressor load steps
affect engine 11 in terms of its NOx emissions and
thermal efficiency. The test resulting in the data of
FIGURE 4 was performed for an engine 11 having a constant
10 load, but at different compressor load steps.

The test represented by FIGURE 4 is based on the
principle that engine horsepower is proportional to the
flow pressure difference and the compressor load step
(LS). In other words: HP α $P_{discharge}$ - $P_{suction}$, LS. The
15 same engine horsepower can be achieved by varying the
load step as the suction pressure changes. The
difference between two load steps (Load Step 1 and Load
Step 2) was the deactivation of a head end pocket in one
of four compressor cylinders coupled to an inline six-
20 cylinder engine. As illustrated, the slopes of MAP
(manifold intake pressure) versus NOx emissions are
different for different load steps.

As further indicated in FIGURE 4, the NOx emissions
varied between the two load steps for several spark
25 timings, even though the load on the engine remained the
same. For each load step, the spark timings were 2, 4,
and 6 degrees before TDC (top dead center).

At Load Step 1, all compressors have equal clearance
volume; all compressor pockets are closed. In Load Step
30 2, an additional 1410 cubic inches of clearance volume
was created by the deactivation of the head end pocket in

one of the compressor cylinders. The deactivation
unloads one or more power cylinders because the gas in
that compressor cylinder is being compressed to a lower
pressure than the gas in the other compressor cylinders.

5   The test results illustrated in FIGURE 4, and the
results of similar tests, indicate that air and/or fuel
flow is sufficiently perturbed by uneven compressor loads
so as to cause changes in engine combustion
characteristics. This belies the conventionally held
10   belief that engine combustion characteristics are
substantially similar so long as the overall engine load
(horsepower) remains the same.

        The present invention is based on a principle of
providing fuel flow and spark timing modulation among
15   power cylinders for the purpose of compensating for
unevenly distributed compressor loads or load steps.

        An important engine control compensation is normally
for fuel flow, due to the varying air flow caused by the
speeding up and slowing down of the engine crankshaft
20   during the engine cycle. This leads to increased or
decreased air charging in two stroke engines because the
engine piston speed increases and decreases, leading to
longer or shorter times that the intake ports are open
for air scavenging. If fuel flow is constant for all
25   power cylinders, the trapped air-fuel ratio is not
constant among the power cylinders. However, if fuel
flow and ignition timing compensations are made, similar
combustion characteristics across the power cylinders can
be achieved.

30   To this end, controller 17 receives various input
data representing operating conditions of engine 11 and

compressor 12. Controller 17 then processes this data to determine various control parameters for engine 11 and compressor 12.

Input data from engine 11 may include, without

5   limitation: engine speed, intake manifold air pressure and temperature, engine coolant temperature, exhaust back pressure, pre-turbine pressure, exhaust gas NOx concentration, exhaust gas oxygen (O2) concentration, air flow to engine, fuel flow to engine, ignition system

10   energy, as well as other inputs required to optimize engine control. Input data from compressor 12 may include, without limitation: load steps on each cylinder, suction pressure, discharge pressure, and suction and discharge temperatures.

15   Controller 17 is programmed with engine control algorithms that optimize performance of engine 11, based on compressor load step conditions and other performance data. Compressor load step algorithms are based on desired pipeline pressure or flow throughput, with the

20   goal of balancing compressor loads across the engine and/or minimizing the effects of unbalanced compressor loads on engine performance. Typically, engine optimization is in terms of fuel consumption and exhaust emissions. However, controller 17 may be programmed to

25   achieve any combination of one or more engine optimization goals.

Various engine control parameters that are subject to control by controller 17 include, without limitation: and ignition timing, the number of spark/ignition events

30   per cycle and per power cylinder, fuel quantity, fuel injection or admission timing per cycle and per power

cylinder, the number of fuel injection events per firing
event, global and per cylinder pre-chamber fueling
quantity, global and per cylinder pre-chamber fueling
rate, global and per cylinder pre-chamber fuel pressure,
5   global and per cylinder air-to-fuel and equivalence
ratio, air flow to the engine (intake manifold pressure),
and turbocharger wastegate parameters. Additionally, if
engine 11 is equipped with pilot injectors, controller 17
may control the pilot injection quantity and/or timing
10 per cycle and per power cylinder.

    Various compressor control parameters that are
subject to control by controller 17 include, without
limitation: compressor load step, compressor pocket
position, compressor load step sequence, compressor
15 suction and/or discharge bottle conditions, and pipeline
yard conditions.

    For both the engine and compressor, controller 17
may be programmed to determine the various control
parameters for steady state and/or transient engine
20 conditions. More specifically, during actual engine
operation, the engine is often operating under transient
conditions regarding load and speed. For example,
during steady state conditions, there is a balance
between the fuel flow from the injectors and the fuel
25 flow to the cylinders which is not present during
transient conditions. One of the challenges of engine
control is to provide constant control parameters, such
as a constant air to fuel ratio, despite the difficulty
of measuring the air-to-fuel response of the engine under
30 transient conditions. This type of engine control is
sometimes referred to as "transient compensation".

Additionally, the control parameters for engine 11 may be on a "global" or per cylinder basis. If desired, input data representing a current engine or compressor current operating condition can be used to determine a

5   control parameter for that same operating condition, such that controller 17 acts in the manner of a feedback controller.